

Jøtul F 500 V3 Oslo





# JØTUL F 500 V3 OSLO

---

## FEATURES

- EPA 2020 Certified
- Jøtul Fusion™ technology creates a clean burning wood-stove that operates without the need for a bypass
- Closer clearances to combustibles than “Hybrids” because there is no open bypass mode
- Not draft sensitive like typical catalytic systems
- High flow Jøtul combustor eliminates “back puffing”
- High flow Jøtul combustor resists ash and soot accumulation
- The Jøtul combustor begins to clean up the emissions almost immediately as there is no way to bypass the combustor
- Efficiency: LHV 84.7% HHV 78.4%
- Weighted average particulate emissions rate of 0.5 g/hr.
- Max heating output: 70,000 BTU\*
- Heating capacity: Up to 2,300 sq.ft.
- Burn time: Up to 12 hrs
- Log size: Up to 24”
- Firebox size 2.54ft<sup>3</sup>
- Stove dimensions: 28 1/2”H x 28 1/4”W x 22 1/2”D
- Minimum hearth dimensions: 54 1/2”W x 50 1/2”D
- Standard bottom heatshield
- 10 year combustor warranty covering against manufacturing defects and materials



---

## OPTIONS

- Short leg kit for fireplace installations (reduces height by 2 1/4”)
- Blower fan kit (120 cfm)
- Cookplate
- Leg leveler kit
- Rear heatshield
- Stove top thermometer
- Stove gloves
- Choice of 3 colors (Majolica Brown Enamel, Blue Black Enamel(Only in Lattice Door unit) or Matte Black Paint)

- Jøtul has a policy of constant improvement and upgrading. Products therefore may differ in specification, design, material or dimensions at any time without prior notice.
- “The maximum heat output value is representative of a refueling cycle which may be used by the home owner that would be more frequent than prescribed by the certification testing method.”

TIMELESS NORWEGIAN CRAFT

