

Jøtul GF 160



# JØTUL GF 160

## FEATURES

- Cast iron “convex-triangle” direct vent gas stove with multi-sided fire-viewing
- Integrated Invisimesh™ safety screen allows for unobstructed view of the fire
- Large 3 sided fire-view
- Revolutionary JøtulBurner™III delivers unsurpassed burner technology and flame picture realism
- Multifunction Proflame 2 remote with flame modulation control
- Top firing accent light kit(remote controlled with 6 levels)
- Blower Kit (remote controlled with 6 levels)
- Choice of required media includes Traditional Logs, River Rocks, Tumbled Stones, Black Glass, and White Starfire Glass.



## OPTIONS

- Choice of interior panels (Reflective glass or Skamol)
- Choice of two colors: Matte Black Paint or White enamel

## TECHNICAL SPECIFICATIONS

Heating Capacity <sup>1</sup>	Up to 700 sq.ft.
Min/Max Heat Input (BTU/hr)	15,800-24,000 (NG) 19,800-24,000 (LP)
Efficiency Steady State	74.49%
Efficiency AFUE	66.40%
EnerGuide Rating (Canada only)	67.07% (NG) 67.84% (LP)
Venting	4" x 6 5/8"
Dimensions	
Height	35 1/2"
Width	17 3/4"
Depth <sup>2</sup>	17 3/4"
Clearances	
Rear	3"
Side	7 3/8"
Corner	3 3/8"
Ceiling From Stove Top	33 1/2" (For vertical termination only)

TIMELESS NORWEGIAN CRAFT



• Jøtul has a policy of constant improvement and upgrading. Products therefore may differ in specification, design, material or dimensions at any time without prior notice.

